

GENERATING SET GE 3200 SX

- Honda OHV petrol engine
- Engine shut down for low oil level
- Single-Phase synchronous alternator
- Recessed sockets: 1 x 230V 16A 2P+T CEE - 1 x 230V 16A 2P+T SCHUKO
- ELCB-GFI (Ground Fault Interruptor)
- Overload thermal shut off
- Suitable for electronic equipments
- Protective frame
- Silenced
- Portable
- Meets EC Directives for safety and noise level



| | | | | | | | | | | |
|--------------------|--|--|--|--|--|--|--|--|--|--|
| Standard Equipment | | | | | | | | | | |
| | | | | | | | | | | |

Options on request • 230V Plug

• Earthing kit

Technical data

GE 3200 SX

A.C. GENERATION - 50 Hz

Single-phase synchronous alternator, self-excited, self-regulated, brushless

* Stand-by single-phase power

3.1 kVA (2.8 kW)/ 230 V / 13.5 A

* P.R.P. single-phase power

2.8 kVA (2.5 kW)/ 230 V / 12.2 A

Cos φ

0.9

Battery charger

12Vc.c. - 10A

Insulation class

H

* Output powers according to ISO 8528-1

ENGINE

4-stroke petrol, air cooled, OHV

Model

Honda GX 200

* Stand-By net power

3.7 kW (5.0 HP)

* P.R.P. net power

3.3 kW (4.5 HP)

Cylinders/ Displacement

1/ 196 cm³

Speed

3000 rpm

Fuel consumption (75% of PRP)

1.1 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity

3.1 l

Running time (75% of P.R.P.)

2.8 h

IP protection degree

IP 23

Dimensions LxWxh (mm)

570x420x450 mm

Dry weight

52 kg

*Measured acoustic power LwA (pressure LpA)

95 dB(A)(70 dB(A) @ 7m)

*Guaranteed acoustic power LwA (pressure LpA)

96 dB(A)(71 dB(A) @ 7m)

* Acoustic power according to European Directive 2000/14/EC