

GENERATING SET GE 7554 HSX (EAS)

- HONDA OHV petrol engine
- Engine shut down for low level oil
- Electric starter
- Three phase synchronous alternator IP54
- Output sockets : 1 x 400V 16A 3P+N+T CEE
2 x 230V 16A 2P+T SCHUKO
- Isometer
- Circuit breaker
- Super silenced
- CTM7 (option)
- Prepared for connection to automatic transfer unit
- Meets EC directives for safety and noise level

Standard equipment 											

- Options on request
 - 400 V plug
 - 230V plug
- Earthing kit
 - Automatic transfer unit EAS 15B-806
 - Remote control
- Exhaust extension
 - CTM7 (four wheels)

Technical Data

GE 7554 HSX

A.C. GENERATION - 50 Hz

Three-phase synchronous alternator, self-excited, self-regulated, brushless

* Stand-by three-phase power

7,5 kVA (6 kW) / 400V / 10,8A

* P.R.P. three-phase power

6,5 kVA (5,2 kW) / 400V / 9,4A

* P.R.P. single-phase power

5 kVA / 230V / 21,7A

Cosφ

0,8

Insulation class

H

* Output powers according to ISO 8528-1

ENGINE

4-stroke diesel, OHV, air cooled

Model

HONDA GX 390

* Stand-By net power

7,7 kW (10,5 HP)

* P.R.P. net power

6 kW (8,1 HP)

Cylinders/ Displacement

1 / 389 cm³

Speed

3000 giri / min.

Fuel consumption (75% of P.R.P.)

2,5 l/h

* Maximum output according to ISO 3046-1

GENERAL SPECIFICATIONS

Tank capacity

20 l

Running time (75% of P.R.P.)

8 h

IP protection degree

IP 54

*Dimensions LxWxh (mm)

1060 x 570 x 665 mm

*Dry weight

178 kg

**Measured acoustic power LwA (pressure LpA)

88 dB(A) (63 dB(A) @ 7m)

**Guaranteed acoustic power LwA (pressure LpA)

89 dB(A) (64 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer.

** Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.